


Post covers (optional)



Places to store support raisers and special mounts on both lifting posts



Optimum door stop protection thanks to rubber tube profiles on lifting carriages



Additional post reinforcements



No-base frame design with no tripping hazard, making it easy to clean the floor and to push in vehicles that cannot be driven




Ergonomic two-hand controls



Support arms with asymmetric design, providing optimum door clearance



Automatic support-arm restraint with fine adjustment and manual release



Available in three different total heights



Great flexibility and safety thanks to MAHA support disc plug-in system



Optional support raisers and special mounts for a wide range of vehicles

HL CS 4.0



ELECTROHYDRAULIC, FOR CARS AND VANS UP TO 4 T GROSS WEIGHT



Technical advantages *(supplementary to pages 12, 13)*

- ♦ Reliable and powerful drive combined with low energy consumption
- ♦ Low-maintenance
- ♦ Support arms with large extension length suitable for vehicles ranging from the smallest cars to transporters
- ♦ Short support arms, double-telescoping
- ♦ Optional transporter support arms, 2 pieces
- ♦ Support arms with low minimum pad height
- ♦ Mechanical safety latch, with manual release

'The energy saver'



TECHNICAL DATA

	HL CS 4.0	HL CS 4.0 L	HL CS 4.0 H
Load capacity	4000 kg	4000 kg	4000 kg
Max. lifting height HO	1930 mm	1930 mm	1930 mm
Lifting/lowering time, depending on load, roughly	35/35 s	35/35 s	35/35 s
Minimum pad height, support arm HU	110 mm	110 mm	110 mm
Adjustment range, support disc HT	90 – 125 mm	90 – 125 mm	90 – 125 mm
Extension range, short support arms LK	585 – 1150 mm	585 – 1150 mm	585 – 1150 mm
Extension range, long support arms LL	920 – 1505 mm	920 – 1505 mm	920 – 1505 mm
Extension range, transporter support arms LLT	1100 – 1840 mm	1100 – 1840 mm	1100 – 1840 mm
Total height HG	4178 mm	3625 mm	4778 mm
Clear height to safety edge HL	4010 mm	3460 mm	4610 mm
Total width BG	3486 mm	3486 mm	3486 mm
Outer post width BA	3290 mm	3290 mm	3290 mm
Inside columns BL	2800 mm	2800 mm	2800 mm
Drive-through clearance BH	2450 mm	2450 mm	2450 mm
Unladen weight without packaging	700 kg	700 kg	700 kg
Drive power	2.2 kW	2.2 kW	2.2 kW
Supply voltage	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz	3 x 400 V / 50 Hz
Fuse	16 A, slow-blow	16 A, slow-blow	16 A, slow-blow
Hydraulic oil volume	15 l	15 l	15 l
Packaging dimensions	3950 x 800 x 770 mm	3950 x 800 x 770 mm	3950 x 800 x 770 mm

All models




Support disc raisers, 50 / 100 / 150 / 200 mm

All models



Special vehicle mounts: MB G-Class, support mandrel MB Sprinter/VW Crafter, special prism MB Sprinter/VW Crafter, plug-in system, slippage guard

All models



Stainless steel storage tray for small parts

All models



Mount for impact wrench

All models



Installation accessories/injection anchor system

All models apart from HL CS 4.0



Energy block with electricity and compressed-air connections

MAPOWER II series



Control panel on counter-post

MAPOWER II series



Parallelogram mount

All models



Document holder

ECON III series



Control unit on counter-post with energy set

ECON III 5.0 / ECONLIFT 6500



Wheel grab mounts

ECON III 5.0 / ECONLIFT 6500



Support arm extension support, parallelogram (standard for ECONLIFT 6500)

GLOBAL PLAYER

... in more than 150 countries worldwide

Subsidiaries

MAHA Maschinenbau Haldenwang GmbH & Co. KG
Hoyen 20 | 87490 Haldenwang | Germany

Phone +49 8374 585 0
Fax +49 8374 585 497

sales@maha.de | www.maha.de