

CORGHI A222TI Tyre Changer

- Tubeless air blast inflation system with air accumulation tank. Pedal controlled.
- Pedal controlled inflation gauge with deflation button
- Pneumatic tilting post
- Pneumatic locking mechanism automatically gives vertical and horizontal clearance from the rim to avoid scratches on the face of the wheel
- 2 speed turntable (3 phase machines)
- Powerful bead breaker 15500nm
- Includes plastic jaw protectors and mounting head inserts
- Includes lube, lube brush, container & HD tyre lever
- Can be fitted with low profile help arms
- Optional ATV or M/C adapters
- 100% made in Italy



OPTIONAL ACCESSORIES
SP300 HELPER

100%
MADE IN ITALY



SPECIFICATIONS	
Outside wheel clamping	10" - 22"
Inside wheel clamping	13"-25"
Maximum tyre width	12.5"
Operating pressure	100-125psi
Weight	259kg
Bead breaker max opening	320mm
Drive motor	380v/3ph - 230V 1PH
Warranty	2 Years

CORGHI A224TI Tyre Changer

- Economic high spec top machine for mid - high demand shops
- TI tubeless air blast system
- Attached pedal controlled inflation gauge
- Quality stainless steel bead breaking cylinder
- Pneumatic tilting column
- Extra heavy duty shafts to avoid distortion under load
- Simultaneous pneumatic locking of the horizontal & vertical arm
- Hi torque turn table 1200nm
- Made in Italy



OPTIONAL ACCESSORIES
SP2300 HELPER

100%
MADE IN ITALY



OPTIONAL ACCESSORIES
SP300 HELPER



STANDARD
ACCESSORIES



SPECIFICATIONS	
Rim clamping	10" - 24" External 13" - 26" Internal
Max tyre diameter	1100 mm (43")
Max tyre width	350 mm (14")
Bead breaker cylinder force	2500kg
Max operating pressure	10 bar (140 psi)
Power supply	380V 3PH - 2 Speed
Max spindle torque	1200 Nm
Warranty	2 years