

/// AUTOM THE AUTO EQUIPMENT SPECIALISTS

Automaster AM-202IT

Tyre Changer





Automaster AM-202IT

SERVICE OUR VICE-GRIP GUARANTEE If you're not happy, we replace or refund in full.

Tyre Changer



Rim clamping range from outside 10"- 22" inside 12"- 24"

By adjustable jaws.

This provides a huge range without the need for an oversized turntable





Automaster Tyre machines deliver years of dependability because they are built using only the highest quality components

FEATURES

- The Automaster AM-202IT Pro Series Heavy duty tyre changer provide great value for money.
- It is the perfect changer for workshops that do tyres or an ATV/motorcycle dealer .
- Designed to change the tyres on both high priced alloy wheels and steel wheels without damaging the rim or the tyre
- Pneumatically controlled tilt-back column
- Supplied standard with a pedal controlled inflation gauge and tubeless air blaster system
- Options of a **1 speed 1Ph motor** or **3ph-2 speed** motor.
- Pedal controlled tyre inflation
- Tubeless air blast inflation system with air accumulation tank. Pedal controlled. Each jaw clamp has an angled jet outlet for the tubeless air blaster system.
- **Powerful bead breaker** is designed to break even the most stubborn and rusted beads without damage.
- Pneumatic locking mechanism automatically gives vertical and horizontal clearance from the rim to avoid scratches on the face of the wheel - an essential feature when dealing with alloy wheels.
- Optional HP2 low profile helper arms, or twin helper arms to make changing difficult tyres easy, and help reduce the risk of damage caused by tyre levers.
- Optional ATV or M/C adapters





Tubeless air blast inflation system with air accumulation tank. Pedal controlled. Each jaw clamp has an angled jet outlet for the tubeless air blaster system.


Automaster AM-202IT

SERVICE OUR VICE-GRIP GUARANTEE If you're not happy, we replace or refund in full.


Tyre Changer



SPECIFICATIONS	
Inside wheel clamping	12" - 24" By adjustable jaws
Outside wheel clamping	10"- 22" By adjustable jaws
Maximum tyre diameter	39"
Rim width	3-13"
Motor Power	230v/1ph or 380V 3ph 2 Speed
Turn Table Torque	1200nm







SPECIFICATIONS		
Bead breaker force	3000kg	
Operating pressure	100psi	
Locking mechanism	Pneumatic	
Machine weight	242kg	
Tilting column	Pneumatic	
Warranty	2 Years	

